



The Stelpro duct heater is designed to guarantee maximum operational safety while ensuring comfort and economy. It can be installed in different positions, it is offered in two sizes and it is combined with a deflector kit for better performance and increased versatility. Please contact your local contractor or Hydro-Québec for details on how to save with the dual energy program.

## *Autonomy + savings = dual energy duct heater*

- SUBSTANTIAL SAVINGS**  
thanks to Hydro-Québec's dual energy program (province of Quebec only)
- TEMPERATURE SENSOR**  
for a constant temperature and overheating detection
- INTERLOCK DEVICE**  
prevents the simultaneous start-up of two heating sources
- DEFLECTOR KIT**  
permits to adapt to an existing system
- MULTIPLE INSTALLATION POSITIONS**  
horizontal and vertical

### Features

**COLOR:**

light charcoal

**FINISH:**

galvanized steel

**MANUFACTURING:**

- robust monopiece galvanized steel cabinet
- pilot lights clearly identifies the selected modes
- deflector kit (included)
- plenum temperature sensor (abnormal condition detection)
- diagnostic pilot lights
- each element is protected by a set of thermal cut-outs (manual and automatic)

**WATTAGE & VOLTAGE:**

see the selection table

**HEATING ASSEMBLY AREA:**

- 18 X 16 in.
- 19 X 19 in.

**ELEMENT:**

separately framed elements allowing for quick and easy replacement

**CONTROL:**

- mode selector
- auto transfer function

**INSTALLATION:**

multi-position

**WARRANTY:**

10 years for the elements and 5 years for other components

## Selection table

PRODUCT code	POWER kilowatts	VOLTAGE volts	AMPERAGE amp.	HEATING ASSEMBLY AREA		HEIGHT OA		WIDTH OA		DEPTH OA		PRICE
				mm	in.	mm	in.	mm	in.	mm	in.	
SB05211	5/3.8	240/208	20.8/18.1	406 X 457	16 X 18	319	12 9/16	511	20 1/8	522 - 548	20 9/16 - 23 9/16	504.50
SB05212	5/3.8	240/208	20.8/18.1	483 X 483	19 X 19	319	12 9/16	511	20 1/8	522 - 548	20 9/16 - 23 9/16	576.75
SB10211	10/7.5	240/208	41.7/36.1	406 X 457	16 X 18	319	12 9/16	511	20 1/8	522 - 548	20 9/16 - 23 9/16	588.00
SB10212	10/7.5	240/208	41.7/36.1	483 X 483	19 X 19	319	12 9/16	511	20 1/8	522 - 548	20 9/16 - 23 9/16	676.75
SB15211	15/11.3	240/208	62.5/54.2	406 X 457	16 X 18	319	12 9/16	511	20 1/8	522 - 548	20 9/16 - 23 9/16	654.50
SB15212	15/11.3	240/208	62.5/54.2	483 X 483	19 X 19	319	12 9/16	511	20 1/8	522 - 548	20 9/16 - 23 9/16	754.50
SB18211	18/13.5	240/208	75/65	406 X 457	16 X 18	319	12 9/16	511	20 1/8	522 - 548	20 9/16 - 23 9/16	710.00
SB18212	18/13.5	240/208	75/65	483 X 483	19 X 19	319	12 9/16	511	20 1/8	522 - 548	20 9/16 - 23 9/16	810.00
SB20211	20/15	240/208	83.3/72.2	406 X 457	16 X 18	319	12 9/16	511	20 1/8	522 - 548	20 9/16 - 23 9/16	754.50
SB20212	20/15	240/208	83.3/72.2	483 X 483	19 X 19	319	12 9/16	511	20 1/8	522 - 548	20 9/16 - 23 9/16	865.75
SB23211	23/17.3	240/208	95.8/83.1	406 X 457	16 X 18	319	12 9/16	511	20 1/8	522 - 548	20 9/16 - 23 9/16	810.00
SB23212	23/17.3	240/208	95.8/83.1	483 X 483	19 X 19	319	12 9/16	511	20 1/8	522 - 548	20 9/16 - 23 9/16	932.25
SB27211	27/20.3	240/208	112.5/97.5	406 X 457	16 X 18	319	12 9/16	511	20 1/8	522 - 548	20 9/16 - 23 9/16	943.50
SB27212	27/20.3	240/208	112.5/97.5	483 X 483	19 X 19	319	12 9/16	511	20 1/8	522 - 548	20 9/16 - 23 9/16	1076.75
SB30211	30/22.5	240/208	125/108.3	406 X 457	16 X 18	319	12 9/16	511	20 1/8	522 - 548	20 9/16 - 23 9/16	1010.00
SB30212	30/22.5	240/208	125/108.3	483 X 483	19 X 19	319	12 9/16	511	20 1/8	522 - 548	20 9/16 - 23 9/16	1154.50

Prices indicated in this catalogue are valid 90 days starting from May 1<sup>st</sup>, 2012. For all the updated prices, please refer to the Web site.



## Mode adjustments

<b>transfer temp. function (abnormal condition)</b>	if the heating mode does not meet the demand, this function will automatically activate the other heating mode
<b>electric mode</b>	only the duct heater is used
<b>dual energy mode</b>	heating mode changes automatically depending on the temperature outside
<b>fossil fuel mode</b>	only fossil fuel is used

## Installation

